

## TECHNICAL DATASHEET

**Introduction:** **UltraLite 60** is an ultra lightweight symmetrical fire barrier designed to provide compartmentation in roof cavities and concealed spaces for both vertical and horizontal applications.

**UltraLite 60** is simple to fit and requires no specialist tools or fittings.

**Physical Properties:**

Description:	Lightweight / Health Safe / User friendly / flexible / durable / Easy to shape and cut
Colour:	White
Proprietary Treatment:	Food safe and non-corrosive.
Thickness:	6.5 mm
Weight:	1334 g/m <sup>2</sup> -
Fibre Diameter	> 6 micron, (classified non-respirable)

**Certification Body:** **IFC** Certification Ref. # **1336**

**Test and Assessment Authority:** Exova Warringtonfire Test Reference Ref # **380635**

**Test Specification:** **BS 476: parts 20/22** **60 minutes integrity**  
**15 minutes insulation**

Satisfies the requirements of the *UK Building Regulations: Approved Document B (Fire Safety)* for fire rated cavity barriers.

<b>Packing Specification and Pack Dimensions:</b>	Width:	130cm	Packed: Convoluted and individually wrapped in polythene.  Packed in strong boxes.
	Roll Length:	6m	
	Roll Area:	7.8m <sup>2</sup>	
	Pack Weight:	10.4kgs	
	Quantity per box:	10 packs	
	Quantity per pallet:	2 boxes (20 packs)	