

TECHNICAL DATASHEET



Introduction:

FireHalt Brushseal is a high temperature textile penetration management seal designed to be used exclusively with the full range of Firehalt barrier systems.

FireHalt Brushseal, when correctly installed, will maintain the fire resistant of the chosen Firehalt barrier for up to 120mins.

Firehalt Brushseal is a "one size fits all" tape wrapping product that will suit most sizes and shapes of service penetrations with no wastage.

Physical Properties:	Description:	Lightweight / Health Safe / U <mark>ser</mark> friendly / Flexible / Durable / Easy to Shape, Fit and Cut	
	Colour:	White	
	Proprietary construction:	Non-woven textile / HT glassfibre.	
	Thickness:	4 - 5 mm	
	Weight:	325g/m	
	Fibre Diameter:	> 6 micron, (classified non-respirable)	
Certification Body:	IFC	Certification Ref. #	Pending
Test and Assessment Authority:	Exova Warringtonfire	Test Report Reference :	WF 175941
Test Specification:	BS 476: parts 20/22	Up to 120 minutes Fire Resistance [when combined with a Firehalt barrier system]	
Packing Specification	Roll Width:	145mm	
& Product Dims:	Roll Length:	3m	
	Quantity in box:	4 rolls / 12 lm	
	Box Weight	4kgs	



Culimeta-Saveguard Ltd, +44 (0)161 344 2484 sales@firehalt.com www.firehalt.com



The information on this Data Sheet is provided in good faith. However, the company reserves the right to alter or updatethis data as and when additional information is received. Firehalt products should only be fitted in accordance with the guidelines provided by the manufacturer. Any deviations must be authorised by the manufacturer or their representatives.

Issue No: 1 Page: 1 of 1 Dated: 1 October 2017 File	ef: Prodata firehalt Brushseal v2 .pdf
---	--