

TECHNICAL DATASHEET

Introduction: **UltraLite 60:15** is an **IFC Certified** ultra lightweight symmetrical fire rated cavity barrier designed to provide compartmentation in roof cavities and concealed spaces for both vertical and horizontal applications.

UltraLite 60:15 is simple to fit and requires no specialist tools or fittings.

Physical Properties:

Description:	Lightweight / Health Safe / User friendly / flexible / durable / Easy to shape and cut
Colour:	White
Proprietary Treatment:	Food safe and non-corrosive.
Thickness:	6.5 mm
Weight:	1334 g/m ² -
Fibre Diameter	> 6 micron, (classified non-respirable)

Certification Body: **IFC** Certification Reference # **1336**

Testing Authority: **Warringtonfire**

Test Specification: **Test Classification:** **BS 476: parts 20/22** **60 minutes integrity**
15 minutes insulation

Test Report: **376403 [Vertical]** Expiry date: Jan 2027
380635 [Horizontal]

Packing Specification and Pack Dimensions:

Width:	130cm	Packaging: Convoluted and individually wrapped in polythene.
Roll Length:	6m	
Roll Area:	7.8m ²	Packed in strong boxes.
Pack Weight:	10.4kgs	
Quantity per box:	10 packs	
Quantity per pallet:	2 boxes (20 packs)	