

90:60

PRODUCT OVERVIEW

Firehalt 90:60 is independently certified by KIWA/IFCC, offering 90 minutes of fire resistance when applied horizontally. Its multi-layered construction features specially woven and treated glass fibre fabrics, high-temperature insulation mats, and reflective aluminium foils. The fabric layers and insulation materials are free from respirable fibres, ensuring safe use.

PRODUCT PROPERTIES

Description:	Firehalt 90:60 is a multi-layer fire barrier, that is flexible and durable. Designed for ease of use, the barrier can be cut to fit any shape
Application:	Horizontal use only
Coating:	Weavelock treatment including a proprietary fire-resistant additive which is food safe and non-corrosive
Colour:	White
Minimum Thickness:	18 mm
Minimum Weight:	4900 g/m ²
Fibre Diameter:	> 6 micron (classified non-respirable)

TEST & PERFORMANCE

Testing Authority:	Warringtonfire
Test Classification:	Fire Resistance BS 476: part 2022: 1987 - 90 minutes integrity, 60 minutes insulation
Test Report:	Ref # WF382396 (Horizontal)

PACKAGING

Pack Dimensions:	Width - 130cm
Roll Length:	6m Standard
Roll Area:	7.8m ²
Pack Weight:	38kg (2 Person lift)
Packed:	Convolute and individually wrapped in polythene

CERTIFICATION

Certification Body:	KIWA/ IFCC
Certification Ref:	1337

