

# SF120

## PRODUCT OVERVIEW

Firehalt SF120 is independently certified by KIWA/IFCC. This smoke and flame barrier provides 120 minutes of integrity-only fire resistance, it is tested to both EN1364 (Part 1) and BS476 (Parts 20/22).

Firehalt SF120 is a specially woven / treated glass fibre barrier that contains no respirable fibres, is simple to fit and requires no specialist tools or fittings.

### PRODUCT PROPERTIES

Description:	Firehalt SF120 smoke and flame barrier is flexible and durable. Designed for ease of use, the barrier is easy to handle and can be cut to fit any shape
Application:	Vertical use only
Coating:	Weavelock treatment including a proprietary fire-resistant additive which is food safe and non-corrosive
Colour:	White
Minimum Thickness:	0.5mm
Minimum Weight:	450 g/m <sup>2</sup>
Fibre Diameter:	> 6 micron (classified non-respirable)

### TEST & PERFORMANCE

Testing Authority:	Warringtonfire
Test Classification:	Fire Resistance BS 476: parts 20/22 - 120 minutes integrity only
Test Report:	Ref # 106497
Other Classifications	<ul style="list-style-type: none"> <li>• ISO 1182 1990 (E): Non-Combustibility</li> <li>• IMO Resolution MSC.61(67) Part 1. Non-Combustibility</li> </ul>

### PACKAGING

Pack Dimensions:	Width - 130cm
Roll Length:	25m Standard
Roll Area:	32.5m <sup>2</sup> (Also available in 10m lengths with a roll area of 13m <sup>2</sup> )
Packed:	Rolled on cardboard core and individually wrapped in polythene

### CERTIFICATION

Certification Body:	KIWA/ IFCC
Certified Ref:	# 1334

