

ULTRALITE 60:15

PRODUCT OVERVIEW

Firehalt Ultralite 60:15 is independently certified by KIWA/IFCC. Exclusive to Firehalt, this barrier can be used both vertically and horizontally. It is designed for installation in concealed spaces or roof cavities, serving either as a high-specification cavity barrier or as a fire barrier that extends the fire rating of a compartment wall, reaching up to the roofline or upper floor slab.

PRODUCT PROPERTIES

Description:	Firehalt Ultralite 60:15 is our lightest fire barrier, that is flexible and durable. Designed for ease of use, the barrier is easy to handle and can be cut to fit any shape
Application:	Vertical and Horizontal use
Coating:	Weavelock treatment including a proprietary fire-resistant additive which is food safe and non-corrosive
Colour:	White
Minimum Thickness:	7 mm
Minimum Weight:	1300 g/m ²
Fibre Diameter:	> 6 micron (classified non-respirable)

TEST & PERFORMANCE

Testing Authority:	Warringtonfire
Test Classification:	BS 476: parts 20/22 - 60 minutes integrity, 15 minutes insulation
Test Report:	Ref # 376403 [Vertical], Ref #419257 [Horizontal]
F O A Reports:	(Based on the above test report) <ul style="list-style-type: none"> • Timber Protection Applications Ref #415394_2

PACKAGING

Pack Dimensions:	Width - 130cm
Roll Length:	6m Standard
Roll Area:	7.8m ²
Pack Weight:	10.4kgs
Quantity per box:	10 packs
Quantity per pallet:	2 boxes (20 packs)
Packed:	Convolutted and individually wrapped in polythene

CERTIFICATION

Certification Body:	KIWA/ IFCC
Certified Ref:	# 1336

