

ACCESS HATCH

1200mm x 600mm

PRODUCT OVERVIEW

Firehalt Access Hatch is tested to BS EN 1634-1 fire resistance test standard and provides 60 minutes of integrity-only fire resistance.

It features a unique design with a pre-fitted Firehalt barrier panel for easy integration with Firehalt barriers.

The hatch comprises secure locking features to ensure it remains firmly closed and maintains fire resistance.



WWW.FIREHALT.COM

PRODUCT PROPERTIES

Description:	A heavy-duty steel access hatch designed to simplify installation and integration with Firehalt fire barriers.
Frame & Door tray:	1.2mm Zintec coated
Outer Frame Dimensions:	1200mm x 600mm
Clear Opening:	1160mm x 551mm (with the door at 90 degrees)
Finish:	Polyester powder coated finish
Colour:	White RAL 9010, 20% Gloss
Hatch Fire Rating:	FR60
Hinge Type:	Continuous piano hinge
Locking Mechanism:	Industry standard square drive operated locks that are riveted to the return fold of the door tray with a swivel tongue lock into the frame. Features interlocking active fire pins for enhanced security.

TEST & PERFORMANCE

Testing Authority:	UKTC
Test Classification:	BS EN 1634 – 1:2014_A1:2018 - 60 minutes integrity only
Test Report:	Ref # 20250811-004715

KEY BENEFITS:

Solid construction and heavy-duty hinge provides unobstructed access through the barrier

Secure closure to maintain integrity of fire barrier

Supplied with pre-fitted Firehalt fire barrier panel

Includes interlocking fire pins for enhanced fire security

Independently tested with 60 minutes fire resistance (integrity only, no insulation value)



PACKAGING:

Supplied as a single access panel unit including door panel, frame, lock and panel of Firehalt barrier. Fixings not provided.